



POWERSPIN SUPERIOR SPINDLE OILS

POWERSPIN oils are low viscosity lubricants, blended from highly refined base stocks having excellent oxidation and chemical stability with anti-oxidant, anti-wear, anti-rust and anti-foam additives.

PERFORMANCE STANDARDS: BIS: 493 (Part II) 1981

CHARACTERISTICS	POWERSPIN	
	15	22
ISO VG	15	22
Colour (ASTM)	1.5	1.5
Kinematic Viscosity @ 40°C, cSt	13-16	20-22
Flash point, COC, °C, min.	140	170
Pour point, °C, max.	-3.0	0
Rust test (D-665)	Pass	Pass

APPLICATION:

- Recommended for bearing lubrication of high-speed textile and machine tool spindles, timing gears, centrifugal separators, positive displacement blowers and hydraulic systems of certain high precision machine tools.
- Power Spin 22 is also recommended as anti wear hydraulic oil for systems requiring low viscosity hydraulic fluid.

PERFORMANCE BENEFITS:

- Excellent resistance to rust and corrosion
- Excellent thermal and chemical stability
- Lowest fluid friction
- Excellent anti-wear characteristics of Power Spin 22

(Version # 1 April 14th 2008)

Disclaimer: APAR makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.